




HPS LLC PO Box 855 Rhome, TX 76078

1. Insert a single sheet of media into your printer. Glossy side up for straight path printers, glossy side down for "U" path printers, such as most models by Hewlett Packard. Inserting more than one sheet at a time can cause jams or other complications. For "U" path printers, you may need to gently bend the leading edge of the media in the direction that the printer feeds the media this helps the printer to feed the media properly.



2. In your printer settings, found by selecting "File" then "Print" and then "Properties" select a paper setting so that you print on the media as if you were printing on a piece of premium glossy photo paper. Look for settings such as: "Ultra Premium Glossy Photo Paper" or "Glossy Photo Film" or if your printer doesn't have one of these options, try "Transparency". Also, if you plan on applying the clings to the inside of a window to be read outside you must print in "Mirror image" or "Reverse Image".



3. Allow the ink to dry for at least 25 minutes. The ink may require additional drying time depending on how dense the color is in your art/text. Also, if your printer uses a pigment based black ink, overnight drying may be required. If you intend to use your clings on the inside of the window to be read from the outside, you should apply a white window masking spray directly on top of the printed image/text. This will provide contrast for the clear image and also provide a white background.



4. If your design includes more than one label per sheet, use a very sharp pair of scissors or a craft knife to carefully cut out your individual designs. Cut as close to the edges of your design as possible to minimize the surrounding clear edge, this will minimize the profile of your label, making it look more like a part of the object.



5. Before applying your label it is critical to always start with a clean surface. Remove any residual dust, dirt, or grease from the surface using a mild cleaner. Allow the surface to dry before applying your label. For best results take your time applying the label, proceeding a bit at a time. Smooth out any air bubbles as they occur, but avoid rubbing the label too hard or smudging can occur.



BONUS TIPS!

- Clear media works well on white or light colored surfaces. Our white media is ideal for dark surfaces.
- The removable adhesive is re-useable. Reapply it to the paper backing for storage between uses.
- If you need a more aggressive adhesive, we offer a permanent clear vinyl SKU: IVFG8511.
- The best way to always avoid a paper jam is to load each sheet individually, one at a time.
- For "U" path printers, try gently curving the sheet in the direction the paper loads to avoid jams.

Disclaimer: Our media has been tested with numerous inkjet printers. The user is responsible for determining suitability with his printer and application. The maximum liability of the seller shall be to replace product found to be defective. Neither the manufacturer nor the seller shall be held liable for any injury, direct or consequential, arising out of the use of, or inability to use this paper/film.